

TEST REPORT

109621 / 13

Date received: 12-10-09
Date of test: 23-11-09
Date of issue: 25-11-09
Sample name: Sedia PIKAIA base a razze



KRISTALIA S.R.L.
VIA CALDERANO 5
33070 BRUGNERA (PN)
ITALY

Rolling resistance - EN 1335-3:2000 - Clause 6.1

Type of castors: H
Test surface: textile floor
Test speed: 50 mm/s
Seat height: lowest position

Test results:

Measured resistance before the fatigue test of castors N	Measured resistance after the fatigue test of castors N	Minimum allowed resistance N
27,4	27	15

Unless otherwise specified, measurement uncertainty expanded to a confidence level of about 95% are $\pm 2,0$ N.

The measurement uncertainties stated in this document have been determined according to UNI CEI ENV 13005:2000. They were estimated as expanded uncertainty obtained multiplying the standard uncertainty by the coverage factor k corresponding to a confidence level of about 95%. Normally $k=2$.

Note: this standard has been withdrawn and superseded by EN 1335-3:2009

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.



Managing Director
Dr. Andrea Giavon

Sample name is declared by the orderer. This report relates to the samples submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.